


DampFinder Compact



Universal device for testing moisture in wood and building materials



- **Versatile measuring device:** For ascertaining moisture in building materials and for quick checks when working with wood
- **Triple scale:** for 2 wood groups and universal index mode
- **Quick localisation of moisture:** comparison measurements can be made in **Indicator-mode** which reveal increasing or decreasing moisture based on a neutral scale.
- **Large LC display** with bar graph and numerical display
- **Sturdy, ergonomically designed rubberised casing:** The device can be comfortably held in one hand, meaning that the measuring spikes can be safely inserted.
- **Self-test function:** A reference measurement in the protective cap verifies the accuracy of the measuring device.
- **Removable protective cap** to protect the measuring spikes against damage during transport.
- **Ambient temperature sensor:** The device shows the current ambient temperature after switching on.
- **Simple one-button operation**
- **Auto power off**
- **Low battery display**

TECHNICAL DATA

MATERIALS	
Wood, aerated concrete, anhydrite screed, cement screed, chalky sandstone, concrete (C12/15, C20/25, C30/37), gypsum plaster	
MEASUREMENT RANGE / ACCURACY	
WOOD	± 1% (5%...30%) ± 2% (30%...50%)
INDEX	± 10 digits
OPERATING TEMPERATURE 0° ... 40°C	
STORAGE TEMPERATURE -10°C ... 70°C	
MAX. RELATIVE HUMIDITY 85%	
POWER SUPPLY	
Batteries 4 x 1,5 V Typ AAA	
WEIGHT (incl. batteries) 183 g	
DIMENSIONS (W x H x D) 58 mm x 155 mm x 38 mm	



Large, clear LCD

Simple one-button operation

Protective cap with self-test function



DampFinder Compact
+ batteries (4 x 1,5V AAA)
+ protective cap with self-test function
Packing dimension (W x H x D)
–

ARTICLE	ARTICLE NO	EAN-CODE	PU
DampFinder Compact	082.015A	4 021563 690015	5

4x
AAA